Epson ColorWorks[™] C3500 Color Inkjet Label Printer



- Compact, robust design for commercial use
- High print speed of up to 4 inches/second¹
- High-quality, four-color inkjet printing (CMYK)
- Individual ink cartridges for efficient use of ink
- Supports all major label applications
- Meets BS5609 certification²
- USB and Ethernet interfaces

Now you can dramatically reduce label costs, increase operational efficiencies and quickly produce high-quality color labels with Just in Time Color[™] printing on Epson's high-speed ColorWorks C3500 printer.

Color labels are the new standard

Today there is a growing demand for the use of color labels that feature color codes, photos and pictograms to highlight relevant information. This trend sharply drives up the number of label variations and increases label production complexity. Epson's ColorWorks C3500's ability to produce full color labels on demand makes it the ideal solution.

Advanced features only from Epson

Epson's compact, four-color C3500 inkjet printer features fast printing speeds up to 4 inches/second, a banding reduction mode and a nozzle check system that produces a reliable output of high volume labels with excellent image quality. In addition, it offers multiple easy-to-use features such as an autocutter, easy paper loading and an LCD with printer status readouts.

Superior print and ink quality

Epson's patented MicroPiezo® inkjet technology together with our DURABrite® Ultra Pigment ink ensures labels with crisp, clear, easy-to-read text and barcodes and vibrant graphics that resist smudges and water even on plain paper. And with the C3500 you can print on a wide range of media from plain, synthetic and matte to glossy stock. It handles roll-fed or fanfold, die cut or continuous label media.

Significantly lower your costs

With Epson's C3500 printer you can dramatically reduce the cost of your label operations. Instead of maintaining an expensive inventory of preprinted labels, you can print the labels you need when you need them. In addition, the C3500 features individual ink cartridges for a more efficient use of ink and a very low cost of maintenance.

Reliable and flexible

Designed for high-duty commercial environments, the rugged C3500 is dust and water-resistant and built to last. It has an MTBF of 88 thousand hours.³

Backed by the leader

The ColorWorks C3500 delivers the quality and reliability that Epson is known for and is backed by Epson's industryleading service and support programs.





Fast, Full-Color Label Printer for Just in Time Color Printing

Printer

Print method	MicroPiezo® inkjet technology, Automatic Nozzle Checking				
Ink type⁴	Pigmented ink, individual CMYK cartridges				
Print resolution	360 dpi x 360 dpi — Speed Mode 720 dpi x 360 dpi — Quality Mode				
Print speed (max.)	360 dpi x 360 dpi — Banding Reduction disabled 4.0"/sec. (2.2" print width) 3.4"/sec. (4.1" print width)				
	360 dpi x 360 dpi — Banding Reduction enabled 3.7"/sec. (2.2" print width) 3.1"/sec. (4.1" print width)				
	720 dpi x 360 dpi — Banding Reduction enabled 2.0"/sec. (2.2" print width) 1.7"/sec. (4.1" print width)				
Print width	4.1" (104mm) max.				
Media types	Roll-fed or fanfold; die cut or continuous; single layer or adhesive labels on liner; plain paper, fine paper, PET film, synthetic				
Media dimensions					
Width	1.2"–4.25" (30–108mm) — roll feed 2.0"–4.25" (50-108mm) — fan fold				
Thickness	4.7–7.5mils (0.12–0.19mm)				
Roll size	O.D. 4.0" (102mm) max. Core diameter 1.75" (44mm) to 2.25" (57mm)				
Media sensors	Gap, black mark, media cut				
Die-cut label gap Black mark size	Min. 0.12" (3.0mm) Min. 0.20 x 0.16" (5.0 x 4.0mm) (W x H)				
General					
Interfaces	USB 2.0 High-speed, Ethernet 10/100 BASE-T				
Operating system	Microsoft® Windows® XP 32-bit (SP3)/64-bit (SP2), Vista® 32-bit/64-bit (SP2), Windows 7 32-bit/64-bit (SP1), Windows 8 32-bit/64-bit				
Barcode font (Built-in driver)	UPC-A, UPC-E, JAN13(EAN), JAN8(EAN), Code39, ITF, Codabar, Code93, Code128, GS1-128, GS1 DataBar Omnidirectional, GS1 DataBar Truncated, GS1 DataBar Limited, GS1 DataBar Expanded, PDF417, QR Code, Maxi Code, GS1 DataBar Expanded, GS1 DataBa Stacked Omnidirectional, GS1 DataBar Expanded Stacked, DataMatrix, Aztec Code ⁵				
Operating temperature	10–35 degrees C / 20–80% RH humidity				
Storage temperature	-20–40 degrees C / 5–85% RH humidity				
Overall dimensions	12.2" x 11.1" x 10.3" (W x D x H) — Printer				

Weight (Approx.)

Power consumption

Rated voltage

Rated frequency

Safety standards

Warranty

Acoustic noise EMI

17.5" x 15.5" x 16.8" (W x D x H) — Shipping 26 lbs (12.2 kg) — Printer (without ink) 41 lbs (12.2 kg) — Shipping 30 W Printing (average printing) 2.5 W Standby 0.3 W Power Off state AC 100-240 VAC 50-60 Hz Approx. 58 dBA FCC / ICES-003 Class B UL60950-1/CSA C22.2 No.60950-1 One year depot repair

¹Speed is printing 2.2" (56mm) width bidirectional mode, with banding reduction disabled in 360 x 360 dpi resolution.

²Epson's ColorWorks C3500 inkjet printer with Epson's DURABrite® pigment inks used in combination with Neenah Kimdura Poly media has been BS5609 certified.

³Failure is a random failure occurring during the random failure period.

*Inkjet cartridge yields vary considerably for reasons including item printed, print settings, temperature and humidity. Yields may be lower when printing infrequently. A variable amount of ink remains in the cartridge after the "replace cartridge" signal. Ink from the first cartridge is used for priming the printer. Ink is used for both printing and print head maintenance.

⁵No character font or 1D/2D code font installed



USB

Epson America, Inc. • 3840 Kilroy Airport Way • Long Beach, CA 90806 • [562] 290-5304 ©2013 Epson America, Inc. EPSON, DURABrite and MicroPiezo are registered trademarks and Epson Exceed Your Vision ergon a point meta, the large of a constraint of the point of the p

07/2013 SD-DSCWC3500-A

What's in the box

ColorWorks C3500	
AC power adapter with line cord	
Full capacity Ink cartridges	and the second s
Sample label roll	10.3"
Media output tray	
Instruction sheet	11.1"
CD with utilities and manuals	12.2"

Ordering information

		Model Number
TM-C3500 Inkjet Printer		C31CD54011
GJIC22P(C) Ink Cartridge	Cyan	C33S020581
GJIC22P (K) Ink Cartridge	Black	C33S020577
GJIC22P (M) Ink Cartridge	Magenta	C33S020582
GJIC22P (Y) Ink Cartridge	Yellow	C33S020583
SJMB3500 Maintenance Box		C33S020580



Color-coded labels enable fast, accurate product identification.

Poode: 112345678 Law 12345-2.5L 0011234	1567	
Methanol Metanol* Methyl alcohol OH,O NMM72.06 CAS 67-56-1 198.0% Made in Japan		EC 200-659-6, EC Label, MOK 1 EN Eighty fammake, Teals, KH, K320425, S 7, S 44, S3627, S 45 Hyphy fammake, Table frame store, and the store and a framework for the store Hyphy fammake, the store of the store of the store of the store Keep container (style); C 40, Keep away from sources of polition - Ne montaing Water would protective of doming and gives at Lace and 4 acid and the store ball and store of the store of the store of the store of t
22 04 gimel, eg: -98, 8p; 64.7, el 0.791 giml, 0.791 giml, el 25, el 200 = 1.32908.1, el 200-		advice immidiately/show the label where possible). DE Leichtentzandich, Giftig: Leichtentzundlich, Giftig beim Einatmen, Verschlack und Beruhnung mit
Assay Spec >99.5%(OC) NMIO4-educing in accordance acetone none detected, aldehydecas CHOCHO <0.0015	Al <0.5 mg/kg Fe <0.5 mg/kg Bi <0.1 mg/kg Ni <0.5 mg/kg Bi <0.1 mg/kg Ni <0.1 mg/kg Ci <0.5 mg/kg Fe <0.1 mg/kg Ci <0.05 mg/kg Sr <0.1 mg/kg Ci <0.05 mg/kg Sr <0.1 mg/kg Ci <0.05 mg/kg Sr <0.1 mg/kg	der Haut, Chillip erreice Gelehr innerveliden Schulders skunk Einsteines, Beurkung mit die Haut und darch Versichuluten Behalten dich geschlassen halten. Von Zundgelein fehr -Notz rauchan. Die der Arbeit geschlassen Bischultzungen zugen Unterlich der Umzuhlassen abschult zurauhmerkenung Angeleines Bischultzungen Freihr der Bischultzungen, Tausgener, Fasilienensteines Teilunge part Inhalten Is pass ein progeton. Turopart darger dirtich zwenschleines frei geschlassen is passe alle progeton. Turopart darger dirtich zwenschleines frei geschleiten der Inhalten. Turopart darger dirtich zwenschleiten Steg gasse part Inhalten in begenet gen impetion. Turopart darger dirtich zwenschleiten Steg gasse part Inhalten.
free acid(as HCOCH) <0.00025% free alkali(as NH3) <0.0001% ketone(as CH3COCH3) <0.001%	Cr <0.02 mg/kg Cu <0.02 mg/kg	contact avec la peau et par ingestion. Conserver le recipient bien ferme. Conserver a f de toute famme ou source d'atricoiles - Ne pas fumer. Porter un vetenient de protectio des gante apergeines. En cas d'accident ou de malaise, consulter immeliaitement un

The C3500 using Epson pigment inks is BS5609 certified for GHS labels.²



www.SixB.com • 12200 Forestgate Dr. • Dallas, TX 75243 • (800) 284-0121 • Marketing@SixB.com • Page 2 of 3



COMPETITIVE COMPARISON

ColorWorks[®] C3500 inkjet label printer vs. cab XC4, VIPColor VP495, Primera LX400, Zebra ZT400 Series

- ✓ Prints single and multiple color labels on demand at 360 x 360 dpi
- Print speeds up to 4 ips
- ✓ Epson DURABrite[®] pigment ink for high-quality, smudge proof labels



Label Printers

Model Comparison

	Epson ColorWorks C3500	cab XC41	VIPColor VP495 ¹	Primera LX4001	Zebra ZT400 Series ¹
Technology	Epson MicroPiezo® inkjet	Kyocera [®] /Rohm [®] -style thin film thermal transfer	HP [®] thermal inkjet	Lexmark [™] thermal inkjet	Kyocera/Rohm-style thin film thermal transfer
Native Resolution	360 x 360 dpi variable drop size	300 dpi fixed dot size	1200 x 1200 dpi fixed drop size	4800 x 1200 dpi fixed drop size	200/300 dpi fixed dot size
Color	СМҮК	Dual monochrome (red/black)	CMY	CMY	Monochrome black
Printhead Life	Permanent head lasts the life of the printer ²	2 million inches	Not stated	Not stated	2 million inches
Head Integrity Check	Nozzle Verification Technology	Not stated	Not stated	Not stated	Not stated
Replacement Printhead Cost	Permanent	\$900 (two heads) plus downtime and service fees	\$495 plus downtime and service fees	\$250 plus downtime and service fees	\$448 plus downtime and service fees
Ink/Ribbon Type	Epson DURABrite pigment ink	Resin ribbon	HP pigment ink	Dye-based ink	Wax resin ribbon
Price (MSRP)	\$1850	\$9075	\$3750	\$1495	\$1795
Estimated Minimum Printer Life	5 Years ³	5 Years	Not stated	Not stated	5 Years
Max. Label Print Width	4.1"	4.1"	8.5"	4.25"	4.25"
Media Types	Roll, fan-fold, die cut	Roll, fan-fold, die cut	Roll, fan-fold, die cut	Roll, fan-fold, die cut	Roll, fan-fold, die cut
Printer Language	Windows® compatible files	Windows compatible files	Windows compatible files	Windows compatible files	ZPL II
Maximum Print Speeds	4 ips	4 ips	3.8 ips	0.15 ips	14 ips
Warranty	12 mo. depot repair	12 mo. depot repair	12 mo. depot repair	12 mo. depot repair	12 mo. depot repair
Extended Warranties Available	Yes	No	No	Yes	Yes

1 Information about competitor products is based on published specifications from the competitor or its technology provider available as of 12/1/2015. | 2 See under Estimated Minimum Printer Life. | 3 Assumes printing 150 km (1 million 4" x 6" labels) over 5 years.

Specifications and terms are subject to change without notice. EPSON, ColorWorks, DURABrite and MicroPiezo are registered trademarks and EPSON Exceed Your Vision is a registered logomark of Seiko Epson Corporation. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Com-CC-Jan-15 Copyright 2015 Epson America, Inc. CPD-50976 12/15

